REPORT DOCUMENTATION PAGE

Form Approved OMB NO. 0704-0188

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggesstions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA, 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any oenalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS

I LLAGE DO N	JI ILLIONIN 1001	TONWIO IIIL A	ADDITESS.				
1. REPORT I	ORT DATE (DD-MM-YYYY) 2. REPORT TYPE		3. DATES COVERED (From - To)				
11-03-2014 R			Related Material	-			
4. TITLE A	ND SUBTITLE			5a. C	ONTRACT NUMBER		
Electron transport and Minority Carrier Lifetime in HgCdSe				W91	W911NF-10-1-0335		
2013 II-VI	Workshop	-	_	5b. G	5b. GRANT NUMBER		
				5c. PROGRAM ELEMENT NUMBER			
				611102			
6. AUTHOR	.S			5d. PROJECT NUMBER			
Kevin Doyl	e, Presenter						
				5e. TASK NUMBER			
				5f. WORK UNIT NUMBER			
					T		
7. PERFOR	MING ORGANI	ZATION NAM	ES AND ADDRESSES		8. PERFORMING ORGANIZATION REPORT		
Texas State	•				NUMBER		
601 Univers	sity Dr.						
San Marcos	TV	7966	66 -4684				
			7 NAME(S) AND ADDRES	20	10. SPONSOR/MONITOR'S ACRONYM(S)		
(ES)	IdiNG/MONTO	KING AGENCI	T NAME(S) AND ADDRES	,,,	ARO		
U.S. Army F	Research Office				11. SPONSOR/MONITOR'S REPORT		
P.O. Box 12					NUMBER(S)		
Research Ti	riangle Park, NC	27709-2211			57432-EL.16		
12. DISTRIE	UTION AVAIL	IBILITY STATI	EMENT				
Approved for	public release;	distribution is un	limited.				
	MENTARY NO						
					and should not contrued as an official Department		
of the Army	position, policy of	or decision, unles	ss so designated by other do	cumentation.			
14. ABSTRA	C T						
		background e	electron concentration is	s Group V	II impurities (Br, Cl, F) introduced from Se		
source mat	•	C		1	1 () / /		
Change in	concentration	with annealin	g suggests p-type Hg va	acancies ar	nd n-type Se vacancies		
15. SUBJEC		naganaana di	stribution of alastrons is	ntraduand :	in arouth raduced with Ha then Co annual		
	I LEKWIS Isport Minority C	Parrier Lifetime l	HGCdSa				
Licetion trai	isport willionty C	arrier Effetime	nocuse				
16 CECLIBE	EV CLASSIFIC	A TION OF:	17 LIMITATION OF	15. NUMI	BER 19a. NAME OF RESPONSIBLE PERSON		
16. SECURITY CLASSIFICATION OF: 17. LIMITATION OF a. REPORT b. ABSTRACT c. THIS PAGE ABSTRACT				OF PAGES			
UU	UU ABSTRACT	UU	UU		19b. TELEPHONE NUMBER		
		100			512-245-6711		

Report Title

Electron transport and Minority Carrier Lifetime in HgCdSe 2013 II-VI Workshop

ABSTRACT

- Major source of HgCdSe background electron concentration is Group VII impurities (Br, Cl, F) introduced from Se source material
- Change in concentration with annealing suggests p-type Hg vacancies and n-type Se vacancies
- QMSA suggests an inhomogeneous distribution of electrons introduced in growth, reduced with Hg-then-Se anneal making mobility more discrete
- Lower electron concentration allows us to see PCD transients, which suggest trap present in as-grown material that is increased with Hg-annealing but removed with Se-annealing, could be Se vacancies
- Lowering background electron concentration and increasing lifetime will require higher purity Se and optimized anneal process

APPROVED FOR PUBLIC RELEASE





U.S. Army Research, Development & Engineering Command

Electron transport and Minority Carrier Lifetime in HgCdSe



TECHNOLOGY DRIVEN. WARFIGHTER FOCUSED.

K. Doyle¹, C. H. Swartz,² J. Pattison,¹ Y.P. Chen,¹ and T. H. Myers²

- Army Research Laboratory, Sensors and Electron Devices Directorate, Adelphi, MD, USA
- 2. Texas State University, MSEC department. San Marcos, TX, USA

Portions of this work were supported by the U. S. Army Research Laboratory and the U. S. Army Research Office under contract/grant number W911NF-10-2-0103, W911NF-10-1-0335, and W911NF-12-2-0019.




APPROVED FOR PUBLIC RELEASE



Alternative IR Material






 HgCdSe is being investigated as an alternative IR material since it is closely lattice-matched to GaSb substrates.

77K As-Grown Concentration








As-grown HgCdSe electron concentration reduced an order of magnitude by switching to higher purity Se source material



SIMS Measurements





Group VII impurities detected, particularly near the ZnTe interface. Could be acting as donors


APPROVED FOR PUBLIC RELEASE

TECHNOLOGY DRIVEN. WARFIGHTER FOCUSED.



Group VII SIMS Concentrations






Reduction in electron concentration corresponds with reduction in Group VII elements detected by SIMS.

Electron Concentration vs. Temperature







- Electron concentration raised after Hg-annealing, lowered after Se annealing, suggests additional p-type Hg vacancies and n-type Se vacancies.
- Appear to have mixed conduction effects at higher temperatures



77K As-Grown Variable Field Hall








$$\sigma_{xx}(B) = \frac{en_1\mu_1}{1 + (\mu_1 B)^2} + \frac{en_2\mu_2}{1 + (\mu_2 B)^2} + \sigma_o$$


$$\sigma_{xy}(B) = -\frac{en_1\mu_1^2 B}{1 + (\mu_1 B)^2} - \frac{en_2\mu_2^2 B}{1 + (\mu_2 B)^2}$$
(\(\mu B\)) <<1






77K Annealed Variable Field Hall








Stage	Element	Temp.	Duration
1	Hg	250 °C	24 hrs
2	Se	250°C	24 hrs

$$\sigma_{xx}(B) = \frac{en_1\mu_1}{1 + (\mu_1 B)^2} + \frac{en_2\mu_2}{1 + (\mu_2 B)^2} + \sigma_o$$

$$\sigma_{xy}(B) = -\frac{en_1\mu_1^2 B}{1 + (\mu_1 B)^2} - \frac{en_2\mu_2^2 B}{1 + (\mu_2 B)^2}$$

$$(\mu B) <<1$$



K. Doyle, Doctoral Dissertation, WVU Library (2013).

APPROVED FOR PUBLIC RELEASE



Multi-Carrier Fit Results




	As-	Hg-	Se-	Hg, then Se	
Parameter	Grown	Annealed	Annealed	Annealed	Unit
n ₁	1.48	3.95	1.70	1.71	x10 ¹⁶ cm ⁻³
μ_1	21,304	13,973	22,205	23,298	cm ² /Vs
n ₂	4.40	4.21	1.23	0.85	x10 ¹⁶ cm ⁻³
μ_2	4,285	4,279	6,233	6,429	cm ² /Vs
σ_1	50.5 I	88.42	60.47	63.82	1/Ωcm
σ_{2}	30.20	28.86	12.28	8.75	1/Ωcm
$\sigma_{ m o}$	13.66	7.17	5.87	4.20	1/Ωcm
σ_1	53.52	71.05	76.91	83.13	%
σ_2	32.00	23.19	15.62	11.40	%
$\sigma_{ m o}$	14.47	5.76	7.47	5.47	%



78K Minority Carrier Lifetime ARE








78K Lifetime vs. Doping





- Transients were fitted. For samples with more than one slope, the first slope was taken as the photo-conductance lifetime.
- As electron concentration decreased with annealing, lifetime increased.
- Longest 77K lifetime was observed for sample annealed under Hg then Se (220 ns)

Summary and Future Work ARI




- Major source of HgCdSe background electron concentration is Group VII impurities (Br, Cl, F) introduced from Se source material
- Change in concentration with annealing suggests p-type Hg vacancies and n-type Se vacancies
- QMSA suggests an inhomogeneous distribution of electrons introduced in growth, reduced with Hg-then-Se anneal making mobility more discrete
- Lower electron concentration allows us to see PCD transients, which suggest trap present in as-grown material that is increased with Hg-annealing but removed with Se-annealing, could be Se vacancies
- Lowering background electron concentration and increasing lifetime will require higher purity Se and optimized anneal process



77K Hall Mobility






As-grown HgCdSe electron mobility comparable to HgCdTe of similar electron concentration.

Electron Mobility vs. Temperature








Electron mobility raised/lowered with concentration after anneal

Lifetime vs. Temperature










Br concentration (SIMS)








CI concentration (SIMS)








F concentration (SIMS)









77K Hg-Annealed Variable Field Hall








Stage	Element	Temp.	Duration
1	Hg	250 °C	24 hrs

$$\sigma_{xx}(B) = \frac{en_1\mu_1}{1 + (\mu_1 B)^2} + \frac{en_2\mu_2}{1 + (\mu_2 B)^2} + \sigma_o$$

$$\sigma_{xy}(B) = -\frac{en_1\mu_1^2 B}{1 + (\mu_1 B)^2} - \frac{en_2\mu_2^2 B}{1 + (\mu_2 B)^2}$$


$$(\mu B) <<1$$






77K Hg-Annealed Variable Field Hall







Stage	Element	Temp.	Duration
1	Se	250 °C	24 hrs

$$\sigma_{xx}(B) = \frac{en_1\mu_1}{1 + (\mu_1 B)^2} + \frac{en_2\mu_2}{1 + (\mu_2 B)^2} + \sigma_o$$

$$\sigma_{xy}(B) = -\frac{en_1\mu_1^2 B}{1 + (\mu_1 B)^2} - \frac{en_2\mu_2^2 B}{1 + (\mu_2 B)^2}$$
(\(\mu B\)) <<1

